

Anti-Vandal Dome Camera, 25MDD Series



Main Features

2.5" Anti-vandal dome
23 Φ 5LEDs
6mm board lens (3.6 mm lens is optional)
IR Distance 25m
weight: 0.5kg
Vandal proof outdoor IR dome camera
360 degree's pan rotation, 90 rotation (manual adjust)

Specification

Model Number	VG-SH42IR25MDD	VG-SO32IR25MDD	VG-SO48IR25MDD	VG-SO54IR25MDD
Image Sensor	1/4" SHARP CCD	1/3" SONY SUPER HAD CCD		
Signal system:	PAL/NTSC			
Horizontal resolution	420 TVL	480 TVL	540 TVL	
Min Illumination	0 LUX			
S/N Ratio	More than 48dB(AGC off)			
Shutter Speed	NTSC=1/60-1/100,000 seconds; PAL=1/50-1/100,000 seconds			
Video Output	1 Vp-p75 ohm			
Power	DC 12V			
Current	270 mA			
Lens	6mm lens			
IR LEDs	23 Φ 5LEDs			
IR distance	25M			
Operation temp	-10 to 50 (centigrade degree)			
Storage temp	20 to 60 (centigrade degree)			
Gross weight	0.5 KG with bracket			