

IR Bullet Camera A-20 M Series



IR Distance 20m

Main Features

Latest designed model

Housing and bracket are designed all-in-one, the cables can not be cut easily by destroyer

3-AXIS universal bracket, it facilitates the installation

Built with 23 Φ 5 Led's, 3.6 mm lens

Dual glasses

Model No.	VG-ASO32IR20M	VG-ASO48IR20M	VG-ASO54IR20M	VG-ASH42IR20M
Image Sensor	1/3" SONY SUPER HAD CCD			1/4" SHARP CCD
Signal system:	PAL/NTSC			
Horizontal resolution	420 TVL	480 TVL	540 TVL	420 TVL
Min Illumination	0 LUX			0 LUX
S/N Ratio	More than 48dB(AGC off)			
Shutter Speed	NTSC=1/60-1/100,000 seconds; PAL=1/50-1/100,000 seconds			
Video Output	1 Vp-p75 ohm			
Power	DC 12V			
Current	250 mA			
Lens	3.6 mm Lens			
IR LEDs	23 Φ 5 LEDs			
IR distance	20M			
Operation temp	-10 to 50 (centigrade degree)			
Storage temp	20 to 60 (centigrade degree)			
Gross weight	0.4 kg with bracket			
Dimensions	Φ 82x128(L)mm			