

## Main Features



Power supply: DC 12V  
 Current: 550 mA  
 B.L.C control: auto  
 LED : 35  $\Phi$ 8 LEDs  
 Lens: 12 mm fixed lens  
 IR Distance: 60 m  
 Come 3-AXIS bracket  
 size:  $\Phi$ 94x152(L)mm  
 weight: 1.1 kg

Housing and bracket are designed all-in-one, the cables can not be cut  
 Built with 3-Axis bracket, it will facilitate your installation  
 With dual glasses technology, it will avoid any possible IR reflection

## Specification

Model No.	VG-CSO32IR60M	VG-CSO48IR60M	VG-CSO54IR60M	VG-CSH42IR60M
Image Sensor	1/3" SONY SUPER HAD CCD			1/4" SHARP CCD
Signal system:	PAL/NTSC			
Horizontal resolution	420 TVL	480 TVL	540 TVL	420 TVL
Min Illumination	0 LUX			0 LUX
S/N Ratio	More than 48dB(AGC off)			
Shutter Speed	NTSC=1/60-1/100,000 seconds; PAL=1/50-1/100,000 seconds			
Video Output	1 Vp-p75 ohm			
Power	DC 12V			
Current	550 mA			
Lens	12 mm Lens			
IR LEDs	35 $\Phi$ 8 LEDs			
IR distance	60 M			
Operation temp	-10 to 50 (centigrade degree)			
Storage temp	20 to 60 (centigrade degree)			
Gross weight	1.1 kg with bracket			
Dimensions	$\Phi$ 94x152(L)mm			