


# IR Bullet Camera G-20 M Series



Weatherproof IR camera with 3-Axis bracket  
IR Distance 20 M



## Main Features

Housing and bracket are designed all-in-one, the cables can not be cut easily by destroyer  
Built with 23  $\Phi$ 5 Led' s, 6 mm lens IR Distance 25 m  
With dual glasses technology, it will avoid any possible IR reflection  
IR auto-open by CDS control in low lux

## Specification

Model No.	VG-GSO32IR20M	VG-GSO48IR20M	VG-GSO54IR20M	VG-GSH42IR20M
Image Sensor	1/3" SONY SUPER HAD CCD			1/4" SHARP CCD
Signal system:	PAL/NTSC			
Horizontal resolution	420 TVL	480 TVL	540 TVL	420 TVL
Min Illumination	0 LUX			0 LUX
S/N Ratio	More than 48dB(AGC off)			
Shutter Speed	NTSC=1/60-1/100,000 seconds; PAL=1/50-1/100,000 seconds			
Video Output	1 Vp-p75 ohm			
Power	DC 12V			
Current	250 mA			
Lens	3.6 mm Lens			
IR LEDs	23 $\Phi$ 5 LEDs			
IR distance	20M			
Operation temp	-10 to 50 (centigrade degree)			
Storage temp	20 to 60 (centigrade degree)			
Gross weight	0.4kg with bracket			
Dimensions	$\Phi$ 69x126(L)mm			